

Over

www.walzenindia.com

35 **YEARS** of Trust

WALZEN

An ISO 9001 - 2015 Company

WHO WE ARE

WALZEN STRIPS PVT. LTD., a medium scale Enterprise incorporated in 1989 commenced commercial production in 1991. Promoted by Late T. Roychowdhury, Technical Entrepreneur, Walzen started with a narrow width Cold Rolling unit at Benaras Road, Howrah in 1992 with a capacity of 3600 TPA. Further in 1996 developed in-house technology for manufacturing High Tensile Steel Strapping and Hardened & Tempered Steel Strips .

Walzen carried out further expansion in the year 2000 to enhance the capacity of Cold Rolled Steel Strips to 15000 TPA, HTSS – 11000 TPA, Hardened & Tempered steel strips – 4000 TPA. Further expansion was done by adding 1 HTSS plant, thereby increasing capacity to 15500 MTPA. Present turnover is about INR 100 Crores, manpower strength is about 600 pan India. All Plant and machineries were meticulously designed and manufactured within the group. The organisation with global presence is now headed by Mr. Indradeep Roychowdhury and is managed by Group COO and VP Mr. Yogesh Lambat.

The Company has a track record of profitable and sustainable growth since inception and is a dividend paying firm. Over years, the production capacity of the various categories of value added products has increased substantially and the aggregated existing capacity now stands at more than 18000 MTPA.

The Company is managed by the whole time Director (Shareholder) and Non Executive Directors, well assisted by a team of COO, CMO, CFO and qualified Technocrats.

ABOUT US

We are partners with world leading and reputed Strapping Tools and Machine Manufacturers. Our product line represents the top manufacturers in the industry, which ensures quality products and the best of service to our Customers. Walzen offers the complete range of steel strapping tools for all kind of packaging applications. We are committed to provide the prompt and an effective solution for our customer's packaging needs with the robust quality tools.

Our Service team consisting of Factory Trained Engineers who work with each client to select the strapping tool and packaging solution that is most effective for their application.

We care for safety and security of your Products through our packaging solutions.



MANUAL SEALER HD

MODEL NO.: ZTMSD – 32127

FEATURES

- Heavy duty Manual Steel Strap Sealer
- Double Notch side action reverse type (up cut)
- High strength Aluminium-alloy handle used
- Operation friendly and less maintenance required

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Weight	Dimension (L X W X H)
0.79 mm – 1.27 mm 0.031" – 0.050"	31.75mm 1 1/4"	High Tensile	75% to 80%	3.90 kg / 8.59 lb	759 x 36 x 101mm 29.8" x 1.41" x 3.97"



MANUAL SEALER

MODEL NO.: ZTMSD – 32089

FEATURES

- Heavy duty Manual Steel Strap Sealer
- Double Notch side action reverse type (up cut)
- High strength Aluminium-alloy handle used
- Operation friendly and less maintenance required

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Weight	Dimension (L X W X H)
0.79 mm – 0.89 mm 0.031" – 0.035"	31.75mm 1 ¹ / ₄ "	Regular Duty or High Tensile	75% to 80%	3.95 kg / 8.7 lb	755 x 70 x 170 mm 29.7" x 2.75" x 6.6"



PNEUMATIC SEALER

MODEL NO.: ZTPS – 19089


FEATURES

- Medium duty Pneumatic Steel Strap Sealer
- Single Notch reverse type (up cut)
- Operation friendly and less maintenance required

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Operating Air Pressure	Weight	Dimension (L X W X H)
0.64 – 0.89 mm 0.025" - 0.035"	19.05mm 3/4"	Regular Duty or High Tensile	75% to 80%	4.5 – 5.0 kg/cm ²	3.2 kg 7.05 lb	259 x 111 x 253 mm 10.19"x4.37"x9.96"



PNEUMATIC SEALER

MODEL NO.: ZTPS – 25089

FEATURES

- Medium duty pneumatic Steel Strap Sealer
- Single Notch reverse type (up cut)
- Operation friendly and less maintenance required

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Operating Air Pressure	Weight	Dimension (L X W X H)
0.64 – 0.89 mm 0.025" - 0.035"	25.4mm 1"	Regular Duty or High Tensile	75% to 80%	5.5 – 6.0 kg/cm ²	3.2 kg 7.05 lb	259 x 111 x 253 mm 10.19"x4.37"x9.96"



PNEUMATIC SEALER

MODEL NO.: ZTPS – 32089

FEATURES

- Heavy duty Penumatic Steel Strap Sealer
- Single Notch reverse type (up cut)
- Operation friendly and less maintenance required

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Operating Air Pressure	Weight	Dimension (L X W X H)
0.64 – 0.89 mm 0.025" - 0.035"	32mm 1/ 1/4"	Regular Duty or High Tensile	75% to 80%	5.5 – 6.0 kg/cm ²	3.2 kg 7.05 lb	259 x 111 x 253 mm 10.19"x4.37"x9.96"



STEEL STRAP CUTTERS

MODEL NO.: ZTSC – 32127

DESIGN ADVANTAGE

Top Cutter blade is elliptical and manufactured from High grade tool steel and hardened 58-60 Hrc. It has four cutting edges. Bottom cutter blade manufactures from rolled medium carbon steel and hard faced with cobalt base alloy that is why tapered edge does not break and has a longer life span.

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Weight	Dimension (L X W X H)
Up to 1.27 mm 0.050"	Up to 31.75 mm 1 ¹ / ₄ "	Regular Duty or High Tensile	3.85 kg 8.5 lb	700 x 51.6 x 203.8 27.55" x 2.03" x 8"

FEATURES

- Heavy duty Steel Strap Cutter
- Very user friendly and less Maintenance required
- Unique design for withstanding heavy cutting load
- Very less cutting pressure required

Usage-Industrial / Commercial



PNEUMATIC COMBINATION TOOLS

MODEL NO.: ZTPCT – 32089

FEATURES

- Heavy duty combination Tool
- Tensioning, Sealing and cutting operations done in one setting
- Tensioner-Pusher type, achievable tension- 725 kg / 1600 lb
- Sealer-Double reverse notch (up cut)
- Cutter – The cutting operation done by sharing operation
- Very user friendly and less maintenance required
- Less time and manpower required than individual system
- High alloy Aluminium Cylinder body used for safety and less weight
- Widely used in steel industries to packaging bulk materials for sheet, coil packing & pipe bundling etc.
- Used for stationary operation, the tool may be suspended on a spring balancer using suspension bracket
- Inserting of the strap into the tool is easier

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Operating Air Pressure	Weight	Dimension (L X W X H)
0.79 mm – 0.89 mm 0.031" / 0.035"	31.75mm 1/ 1/ 4"	High Tensile	6.0 kg/cm ²	16 kg 35.27 lb	431 x 206 x 251 mm 16.97 "x 8.11" x 9.88 "



MANUAL SEALER

MODEL NO.: ZTMSD – 19089

FEATURES

- Medium duty Manual Steel Strap Sealer
- Double Notch side action reverse type (up cut)
- High strength Aluminium-alloy handle used
- Operation friendly and less maintenance required

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Weight	Dimension (L X W X H)
0.64 mm – 0.89 mm 0.025" – 0.035"	19.05mm 3/4"	Regular Duty or High Tensile	75% to 80%	3.85 kg / 8.48 lb	740 x 70 x 180 mm 29.1 " x 2.75"x 7"



MANUAL TENSIONER

MODEL NO.: ZTMT - 32089

DESIGN ADVANTAGE

Base frame are made of forged alloy Steel

FEATURES

- Medium Duty Pusher type Manual Strap Tensioner
- Very user friendly and can be used in a small space
- Compact feed wheel design allows unlimited strap uptake
- Operation friendly and less maintenance required
- Suitable for Flat, Round surfaces ,irregular shaped packages

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Weight	Dimension (L X W X H)
0.64 mm – 0.89 mm 0.025" – 0.035"	19.05mm - 31.75 mm 3/4" - 1 1/4"	Regular Duty or High Tensile	75% to 80%	3.95 kg / 8.7 lb	755 x 70 x 170 mm 29.7" x 2.75" x 6.6"



MANUAL TENSIONER

MODEL NO.: ZTMT - 32127WL


FEATURES

- Heavy duty windlass type Manual Steel Strap Tensioner
- Base is Aluminium Bronze casting .Movable parts are made from high grade alloy steel and heat treated
- Pre cut strap used
- Operation friendly and less maintenance required

Usage-Unitizing of objects in wagon, container, truck & ship lashing etc.

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Joint Efficiency	Weight	Dimension (L X W X H)
0.79 mm – 1.27 mm 0.031" – 0.050"	31.75mm - 31.75 mm 1 1/4"	High Tensile	75% to 80%	5.6kg / 12.34 lb	560 x 118 x 291 mm 22.04 " x 4.64"x 11.54"



PNEUMATIC TENSIONER

MODEL NO.: ZTPT - 32089

FEATURES

- Pneumatic Pusher type Steel Strap Tensioner with unlimited Strap takeup
- Very user friendly and less maintenance required
- Suitable for M.S or Local strap
- Suitable for use on Flat, Round, Irregular and Narrow Surface
- Extra sharing attachment for cutting the strap

Usage-Industrial / Commercial

SPECIFICATIONS

Strap Thickness	Strap width	Grade	Tension Achievable	Operating Air Pressure	Weight	Dimension (L X W X H)
Up to 0.89 mm 0.035"	19.05 - 31.75mm 3/4" - 1 1/4"	Regular Duty or High Tensile and lubricated	725 kg/1600 lb at 6 kg/cm ² (84 psi)	5.5 - 6.0 kg/cm ²	3.2 kg 7.05 lb	321 x 116 x 126 mm 12.64"x4.56"x4.96"

SOME VALUABLE CUSTOMERS



सेल SAIL



ADITYA BIRLA GROUP

आर.आइ.एन.एल. RINL
VIZAG
STEEL
Pride of Steel



SAINT-GOBAIN

नालको  **NALCO**



TATA STEEL

JINDAL 
STEEL & POWER



ITC Limited

ISO 9001:2015




IS : 5872



WALZEN

Packaging Accessories



WALZEN

WALZEN STRIPS PVT. LTD.

Office :

P-250A, C.I.T. Road, Scheme-VIM, Kolkata-700 054

West Bengal, India

Phone : +91 33 2320 1386 / 4760

E-mail : walzen@walzenindia.com

Works :

Biradingi, Benaras Road, Howrah-711 108

West Bengal, India

Phones : +91 33 2651 4773 / 3396

www.walzenindia.com